




PRODUCT FAMILY SHEET

Celestial Plafond



Celestial Plafond

Dimmable surface mounted ceiling light with PC diffuser and even light output. IP54 waterproof structural design, its an ideal replacement for wet locations. Comes with a switch option between 2700K(default)and 3000K. Dimmable by phasecut or DALI2. QuickConnect for easy installation.

VERSIONS

| Art.No | Effect [W] | Cold Lumen [lm] | Lumen Output [lm] | CCT [K] | Beam Angle [°] | Lens Difuser | CRI [>] | Color | Light Control | Connection |
|-------------------|------------|-----------------|-------------------|------------|----------------|--------------|---------|-------|---------------|--------------|
| 101575-120-3- ddd | 25 | 2900 | 2750 | 2700-3000K | 120° | Opal | 80 | White | LI, DALI2, Pu | QuickConnect |
| 101571-120-3- ddd | 18 | 2100 | 1913 | 2700-3000K | 120° | Opal | 80 | White | LI, DALI2, Pu | QuickConnect |
| 101571-120-3-p | 18 | 2100 | 1913 | 2700-3000K | 120° | Opal | 80 | White | Phase-Cut | QuickConnect |
| 101570-120-3-p | 12 | 1250 | 1350 | 2700-3000K | 120° | Opal | 80 | White | Phase-Cut | QuickConnect |
| 101575-E-S-12 0-3 | 25 | 2900 | 2750 | 2700-3000K | 120° | Opal | 80 | White | Sensor (MW) | QuickConnect |
| 101575-S-120-3 | 25 | 2900 | 2750 | 2700-3000K | 120° | Opal | 80 | White | Sensor (MW) | QuickConnect |