



FDV SPEC SHEET

Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phasecut

Art. no: 102070-100-2-p



Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phas



Art. no: 102070-100-2-p

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	968
Lumen LED (tc=25):	1100
Spredningsvinkel [°]:	100°
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	3
Optikk:	Klar

MONTERING / TILKOBLING

Tilkobling:	Hurtigkobling
Montering:	Vegg

ELEKTRISK DATA

Dimmetype:	Faseavsnitt
Dimming Phasecut Type:	Leading / Trailing edge
Flimmerfri:	Ja
Systemeffekt [W]:	8
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	1
Maks belastning pr kurs - B10:	111
Maks belastning pr kurs - B16:	178
Maks belastning pr kurs - C10:	111
Maks belastning pr kurs - C16:	178
Sokkel :	N/A
Strøm LED [mA]:	180
Spenning LED Min [V]:	30
Spenning LED Max [V]:	40



FDV SPEC SHEET

Talos 1100lm 830 100° 8W Black IP54 w/Sockets Phasecut

Art. no: 102070-100-2-p



PRODUKT

IP-grad:	IP54
Vandal klasse:	IK06
Driftstemperatur [°C]:	-20 - 45
Forventet Levetid :	L80B10: 50 000
Farge :	Sort
RAL:	RAL9005
Lengde [mm]:	180
Høyde [mm]:	85
Bredde [mm]:	85
Vekt [kg]:	0,92
Hoved Materiale:	Aluminium