



Plaza Up&Down 900lm 830 15°-210° 10W BK

Outdoor luminaire with a modern design with up and down light. Beam angles are adjustable from 15°-210° by changing position of flaps. Made of die-cast aluminum.





SPECIFICATIONS System Power [W]: 10W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 830lm Lumen LED (tc=25): 900lm Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black		
CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 830lm Lumen LED (tc=25): 900lm Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	SPECIFICATIONS	
CRI / Ra: 80 Lumen Output: 830lm Lumen LED (tc=25): 900lm Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	System Power [W]:	10W
Lumen Output: 830lm Lumen LED (tc=25): 900lm Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	CCT (Color Temperature):	3000K
Lumen LED (tc=25): 900lm Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	CRI / Ra:	80
Beam Angle: 15°-210° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	Lumen Output:	830lm
Lens (Diffuser): Dimming: None System Voltage [V]: Connection: Mounting: Lifetime [h]: Lumen/W: MacAdam (SDCM): Color: Clear None 230V 50Hz 230V 50Hz 230V 50Hz Liguid Source Wall Laboration: Laboration: Clear None Substitution: Anne Substitution: Substitution: Anne Substitution: Substitution:	Lumen LED (tc=25):	900lm
Dimming: System Voltage [V]: Connection: Mounting: Lifetime [h]: Lumen/W: MacAdam (SDCM): Color: None 230V 50Hz 230V 50Hz 240V 50Hz	Beam Angle:	15°-210°
System Voltage [V]: 230V 50Hz Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	Lens (Diffuser):	Clear
Connection: QuickConnect Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	Dimming:	None
Mounting: Wall Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	System Voltage [V]:	230V 50Hz
Lifetime [h]: L80B10: 100 000h Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	Connection:	QuickConnect
Lumen/W: 76lm/W MacAdam (SDCM): 3 Color: Black	Mounting:	Wall
MacAdam (SDCM): 3 Color: Black	Lifetime [h]:	L80B10: 100 000h
Color: Black	Lumen/W:	76lm/W
	MacAdam (SDCM):	3
Longth From 1	Color:	Black
Lengtn [mm]: 120mm	Length [mm]:	120mm
Height [mm]: 100mm	Height [mm]:	100mm
Width [mm]: 96,8mm	Width [mm]:	96,8mm
Weight [kg]: 0,6kg	Weight [kg]:	0,6kg