



## FDV SPEC SHEET

Office Slim Up&Down

Art. no: 1078-2



# Office Slim Up&Down



A

Art. no: 1078-2

### LIGHT TECHNICAL

|                          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen Output:            | 2690           |
| Lumen LED (tc=25):       | 33640-31560    |
| Beam Angle:              | 95             |
| CCT (Color Temperature): | 3000           |
| CRI / Ra:                | 80             |
| Color Code:              | 830            |
| MacAdam (SDCM):          | 5              |
| Lens (Diffuser):         | Opal           |
| UGR (<=):                | 19             |

### MOUNTING / CONNECTION

|             |          |
|-------------|----------|
| Connection: | Terminal |
|-------------|----------|

### PRODUCT

|                     |                 |
|---------------------|-----------------|
| Ingress Protection: | IP20            |
| Lifetime [h]:       | L80B10: 100 000 |
| Color:              | Black           |
| Length [mm]:        | 1200            |
| Height [mm]:        | 75              |
| Width [mm]:         | 15              |
| Weight [kg]:        | 2,7             |

### ELECTRICAL DATA

|                                      |           |
|--------------------------------------|-----------|
| System Power [W]:                    | 29-13     |
| System Voltage [V]:                  | 230V 50Hz |
| Protection Class:                    | 1         |
| Max load pr circuit - B10:           | 8         |
| Max load pr circuit - B16:           | 16        |
| Max load pr circuit - C10:           | 16        |
| Max load pr circuit - C16:           | 32        |
| Leakage current [mA]:                | 0,45      |
| Inrush current I <sub>max</sub> [A]: | 25        |
| Inrush current time [μs]:            | 250       |
| Current Output [mA]:                 | 1050      |
| Voltage Forward Min [V]:             | 2,9       |
| Voltage Forward Max [V]:             | 3,6       |