



PRODUCT FAMILY SHEET

Pollux



Pollux

Pollux is a surface mounted ceiling light that adopts high lumen SMD LED, fire-rated PC diffuser with even light output. IP54 waterproof structural design, it s an ideal replacement for wet locations. Comes with a switch option between 3000K (default), 4000K and 5700K. QuickConnect for easy installation. All data is based on 4000K.

VERSIONS

| Art.No | Effect [W] | Cold Lumen [lm] | Lumen Output [lm] | CCT [K] | Beam Angle [°] | Lens Difuser | CRI [>] | Color | Light Control | Connection |
|--------------|------------|-----------------|-------------------|----------|----------------|--------------|---------|-------|---------------|--------------|
| 2114-S-120-3 | 15 | 1600 | 1480 (4000K) | 3/4/5700 | 120 | Opal | 80 | White | Sensor (MW) | QuickConnect |
| 2112-120-3 | 18 | 1750 | 1644 (4000K) | 3/4/5700 | 120 | Opal | 80 | White | None | QuickConnect |
| 2112-S-120-3 | 25 | 2800 | 2670 | 3/4/5700 | 120 | Opal | 80 | White | Sensor (MW) | QuickConnect |
| 2113-120-3 | 30 | 3300 | 3150(4000K) | 3/4/5700 | 120 | Opal | 80 | White | None | QuickConnect |