



PRODUCT SHEET

Driver 150mA cc 9W (30-60V) Phasecut AcTec JB&SM

Art. no: D15009NTF



Driver 150mA cc 9W (30-60V) Phasecut AcTec JB&SM



SPECIFICATIONS

System Effekt [W]:	9W
Output Hz:	90000
Standby power P _{sb} (W) <:	1
Flicker metric (P _{st} LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
Flimmerfri:	Ja
CC eller CV:	CC
CC [mA]:	150 - 150mA
CC (driver spenning ut) [V]:	30 - 60V
Maks Spenning ut [V]:	60
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	1 or 2
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	PWM
Maks belastning per kurs - B16:	56
Maks belastning per kurs - C16:	118
Lekkasjestrøm [mA]:	5mA
Startstrøm tid [μs]:	100μs
Produsent:	AcTEC
Tilkobling Primær:	Hurtigkobling
Tilkobling Sekundær:	SM kontakt
Farge :	Hvit
Lengde:	109mm
Høyde:	22mm
Bredde:	40mm
Omgivelsestemperatur [°C]:	-20 - 50